[45] Oct. 7, 1980

[54] WINDOW OR THE LIKE STAYS [75] Inventor: Ronald P. Davis, Wellington, New Zealand [73] Assignee: Interlock Industries Limited, Wellington, New Zealand [21] Appl. No.: 948,022 [22] Filed: Oct. 2, 1978 [30] Foreign Application Priority Data Sep. 30, 1977 [NZ] New Zealand 1853 Nov. 23, 1977 [NZ] New Zealand 1857 [51] Int. Cl.2 E05F 3/2 [52] U.S. Cl. 16/179; 49/24 [58] Field of Search 16/8 V, 193, 49, 5
Zealand [73] Assignee: Interlock Industries Limited, Wellington, New Zealand [21] Appl. No.: 948,022 [22] Filed: Oct. 2, 1978 [30] Foreign Application Priority Data Sep. 30, 1977 [NZ] New Zealand
Wellington, New Zealand [21] Appl. No.: 948,022 [22] Filed: Oct. 2, 1978 [30] Foreign Application Priority Data Sep. 30, 1977 [NZ] New Zealand 1853 Nov. 23, 1977 [NZ] New Zealand 18576 [51] Int. Cl. ² E05F 3/2 [52] U.S. Cl. 16/179; 49/24
[22] Filed: Oct. 2, 1978 [30] Foreign Application Priority Data Sep. 30, 1977 [NZ] New Zealand
[30] Foreign Application Priority Data Sep. 30, 1977 [NZ] New Zealand
Sep. 30, 1977 [NZ] New Zealand 18530 Nov. 23, 1977 [NZ] New Zealand 18576 [51] Int. Cl.² E05F 3/2 [52] U.S. Cl. 16/179; 49/24
Nov. 23, 1977 [NZ] New Zealand
[52] U.S. Cl 16/179; 49/24
16/68, 178, 191, 179; 49/250, 251, 252, 24 160/7
[56] References Cited
U.S. PATENT DOCUMENTS
1,614,166 1/1927 Whitney 49/251 2,763,037 9/1956 Benton et al. 49/250 3,407,434 10/1968 Scott 16/19 3,497,909 3/1970 Davis 16/19 3,789,903 2/1974 Clark et al. 160/2

4,102,012	7/1978	Davis	49/248
FO	REIGN	PATENT DOCUMENTS	
		Australia	
986665	4/1976	Canada	49/251
Primary Ex Attorney, A	caminer gent, or l	-George H. Krizmanich Firm—Young & Thompson	

[57] ABSTRACT

A window stay for adjustable mounting of a window sash into a window frame which comprises a first mounting plate adapted for attachment to the frame of a window and a second mounting plate adapted for attachment to the sash of a window. A carriage is slidably mounted on the first mounting plate. An arm is pivotally connected by one end to the sash mounting plate and by the other end to the frame mounting plate. The sash mounting plate is further pivoted but at a point remote from the pivot coupling the arm to the frame mounting plate to the slidably mounted carriage. Means are provided which cause the carriage to be angularly displaced relative to the frame mounting plate during the initial opening and closing.

18 Claims, 17 Drawing Figures

